



YOUR ILLUMINATION SOLUTION™

60W LED

Driver

EGL Class 2 60W High Efficiency LED Driver



Features:

- ◆ High Efficiency (>85%). Fully compliant with CEC Title 24 / Title 20 requirements.
- ◆ Integral junction box with multiple knockouts for versatile wiring / mounting configurations.
- ◆ Universal input voltage (100 - 277 VAC).
- ◆ Constant voltage output - can be used with any 12VDC LED system.
- ◆ Over current, over voltage and short circuit protected.



EGL Part No.	LE-PS60-12
Input Voltage	100 – 277VAC (50 – 60 Hz)
Input Current	0.7A max
Input Wattage	75W max
Output Voltage	12VDC
Output Current	5A max
Output Wattage	60W max
Efficiency	>85%
Operating Temperature Range	-40C to 65C
Overall Dimensions	10.75”(L) x 2.4”(W) x 1.875”(H)
Compliance	UL Class 2 Recognized Component E341160 (Pending) – dry and damp locations. RoHS



YOUR ILLUMINATION SOLUTION™

60W LED

Driver

EGL Class 2 60W High Efficiency LED Driver



Features:

- ◆ High Efficiency (>85%). Fully compliant with CEC Title 24 / Title 20 requirements.
- ◆ Integral junction box with multiple knockouts for versatile wiring / mounting configurations.
- ◆ Universal input voltage (100 - 277 VAC).
- ◆ Constant voltage output - can be used with any 12VDC LED system.
- ◆ Over current, over voltage and short circuit protected.



EGL Part No.	LE-PS60-12
Input Voltage	100 – 277VAC (50 – 60 Hz)
Input Current	0.7A max
Input Wattage	75W max
Output Voltage	12VDC
Output Current	5A max
Output Wattage	60W max
Efficiency	>85%
Operating Temperature Range	-40C to 65C
Overall Dimensions	10.75"(L) x 2.4"(W) x 1.875"(H)
Compliance	UL Class 2 Recognized Component E341160 (Pending) – dry and damp locations. RoHS